

## Standard Medium Type 2-ply Kraft paper dunnage air bags

Semi-automatic manufacturing lines allow us to manufacture this kraft paper bags in the most efficient way possible.

The performance of the standard medium bags could always comply with all current safety standards for air bags world wide.

We can deliver the standard medium 2 ply bags bags with our own developed **MegaFlow**<sup>®</sup> fast filling, or with our millionfold approved and safe standard valve.

### Technical Data

Inliner material ( bladder)	new technology extruded 105µ Polyethylene ( PE )
Outliner material ( cover)	2 layers of extensionable long fibre kraft paper
Max. filling pressure:	20 kPa / 0.20 bar / 2.9 P.S.I
Burst pressure:	60 kPa / 0.60 bar / 8,7 P.S.I.
Safety factor:	3 ( European standard )
Available width:	60cm · 90cm · 120cm 24inch · 36 inch · 48 inch
Available length:	90 · 120 · 150 · 180 · 210 · 225 · 240 cm 36 · 48 · 60 · 71 · 83 · 88 · 95 inch

### Packing

#### MegaFlow valve

Pallet box size standard	100 x 124 x 96 cm ( 1.1904m <sup>3</sup> )
Pallet box size HQ container	100 x 124 x 110 cm ( 1.364m <sup>3</sup> )
Stack in container	2 pallet box on top

#### Standard valve

Pallet box size standard	100 x 124 x 59 cm ( 0,7316m <sup>3</sup> )
Pallet box size HQ container	100 x 124 x 69 cm ( 0,8556m <sup>3</sup> )
Stack in container	3 pallet box on top

Bags per carton, net and gross weight depend on actual size, more packing details on

[www.oemserv.com](http://www.oemserv.com)



- ISO 9001:2008 certified
- SGS, and ROHS test report
- TÜV certificate
- meet most safety standards
- AAR Level 1 certified
- 100% recyclable
- very user friendly
- Available with standard valve or **MegaFlow**<sup>®</sup> fast filling valve
- many times re-usable
- for dry climatic conditions

