

G 105

Polyester Woven Lashing 32 mm

OEMSERV's woven lashing belts are made of high tensile polyester yarns.

Due to its material characteristics it has low elongation (below 10%), is highly tear proof and absorbs very little moisture.

Furthermore the lashing can be retensioned in case of volume loss in the packaged goods and has a high breaking load, linear and within the system.

Woven lashing belts will not splice, are flexible and universally applicable.

Technical Data

Material:

High tensile polyester yarns, woven, glue coated, pre tensioned and heat dried for higher strength

Belt width	32mm (1 1/4")
Linear breaking strength	2000 daN
Max. system strength	3200 daN
Max. securing load (MSL)	1600 daN (1630 kgf)
Max. strength with buckle	FS-30

Packing types

G105 solo	G105 bulk	G105 cake	G105 dispenser
250 meter loose in polybag	250 meter loose in polybag	125 meter rolled unpacked	2x 125 meter rolled and packed in one dispenser bag
1 polybag per carton - size 37x37x40cm	30 polybags per carton - size 110x80x94cm		2 disp.bags per carton - size 54x54x16cm
45 cartons per pallet - size 112x112x190cm	2 cartons per pallet - size 110x80x190cm	224 rolls per pallet - size 120x80x190cm	48 cartons per pallet - size 112x112x190cm
weights* per bag 10 kg carton 11 kg pallet 480 kg * can vary +/- 5%	weights* per bag 10 kg carton 330 kg pallet 680 kg * can vary +/- 5%	weights* per bag 5,5 kg pallet 1100 kg * can vary +/- 5%	weights* per bag 5,5 kg carton 12 kg pallet 600 kg * can vary +/- 5%
Nature / white item # 8230305P1	Nature / white item # 8230327	Nature / white item # 8230308	Nature / white item # 8230341
Orange item # 8230352	Orange item # 8230352P1	Orange item # 8230358	



- no damage to most surfaces
- no corrosion & easy handling
- low investment cost
- high shock absorption
- a small, manageable system
- limited resistance against lyes and acids
- no risk of injury for shippers and consignees in using or opening the strapping

