



Kuiperstraat 4
 5405 BB Uden (NL)
 tel: +31 (0)413 - 25 79 53
 fax: +31 (0)413 - 25 76 64
 E-mail: sales@safetrans.nl
 www.safetrans.nl

ING bank
 Acc. no.: 682196967
 Swift Code: INGBNL2A
 IBAN: NL15INGB0682196967

Chamber of Commerce
 Oost Brabant: 160.88184

VAT no.: NL8095.94.845.B.01
 EORI no.: 806135335

Safetrans Dunnage Bag Specification Sheet

Date : 01-11-2014

Type : 90 x 120 L

Length: 120 cms.

Width : 90 cms.

Strength:

Working pressure : 0,1 bar or 10 kPa or 1,5 p.s.i.

Bursting pressure : 0,3 bar or 30 kPa or 4,5 p.s.i.

Safety factor : 3

void in cms.	contact surface per bag side in cm ²	working pressure in bar	effective force being exercised against cargo in kgs.
20	8100	0,1	810
30	6500	0,1	650
40	3800	0,1	380

void in cms.	contact surface per bag side in cm ²	bursting pressure in bar	effective force exercised at burst in kgs.
20	8100	0,45	3645
30	6500	0,3	1950
40	3800	0,2	760

Tolerance on length and width is 3,5%